

Weatherproof IR camera with optional Heater and Fan



- ✚ Outdoor weatherproof IP66
- ✚ Up to 700TV Lines
- ✚ 36pcs IR LED
- ✚ Auto White Balance
- ✚ Elegant design
- ✚ Bracket included and cable inside the bracket
- ✚ Built in Heater and fan optional

	FST-79H520-HF	FST-79H420-HF	FST-79HM20-HF	FST-79HM420-HF
Image Sensor	1/3" SONY CCD	1/3" SONY CCD	1/3" CMOS sensor	1/3" CMOS sensor
Resolution	540TVL	420TVL	560TVL	4200TVL
IR Cut Filter	Available upon request			
Scanning System	2:1 Interlace			
Sync. System	Internal			
Video Output Level	1.0 Vp-p (75 Ohm, composite)			
S/N Ratio	More than 50dB (AGC off)			
Lens	3.6mm			
Min. Illumination	0.1lux	0.1lux	0.8lux	0.8lux
BLC	AUTO (3200~10000K)			
AES	1/50~1/12,000 sec.			
White Balance	AUTO			
IR LED	36 units (optional)			
Operation Temperature	No Heater and No fan	-10 °C~50 °C		
	With Heater and fan	-40 °C~60 °C		
Heater	Automatic start at 5 degree and stop at 15 degree			
Supplied Voltage	12VDC (9.6~13.2VDC)			
Net Weight	500g			